

WATER TUBE/PRICE PER FOOT

Diameter		Type K			Type L			Type M	DWV	Nitrogen Charged* ACR/MED	
NOM	O.D.	Hard Lengths	Soft Coils	Soft Lengths	Hard Lengths	Soft Coils	Soft Lengths	Hard Lengths	Hard Lengths	Type K	Type L
1/8"	1/4"	-	-	-	-	-	-	-	-	-	4.47
1/4"	3/8"	3.58	3.72	4.53	3.14	3.16	4.06	-	-	3.86	3.39
3/8"	1/2"	6.43	6.72	7.58	4.60	4.71	6.32	3.64	-	6.77	5.10
1/2"	5/8"	7.54	8.21	9.54	5.61	6.86	8.41	4.14	-	7.88	6.59
5/8"	3/4"	9.29	10.14	11.36	8.07	8.78	10.88	6.04	-	9.90	8.81
3/4"	7/8"	13.79	15.31	17.59	9.15	10.92	12.90	6.71	-	14.70	10.49
1"	1-1/8"	17.94	20.33	23.26	13.42	15.64	17.88	10.30	-	18.73	15.08
1-1/4"	1-3/8"	22.52	24.92	27.64	18.57	21.22	23.72	15.42	16.30	23.35	20.10
1-1/2"	1-5/8"	29.71	32.38	38.39	23.64	27.33	31.99	21.21	20.44	31.36	26.11
2"	2-1/8"	44.22	49.69	59.08	36.99	43.49	50.45	32.62	26.81	46.35	39.40
2-1/2"	2-5/8"	65.01	-	88.22	52.95	-	69.24	47.26	-	69.01	56.63
3"	3-1/8"	89.73	-	122.75	73.94	-	92.56	62.76	46.49	93.61	76.55
3-1/2"	3-5/8"	114.78	-	-	96.46	-	-	84.81	-	121.61	101.06
4"	4-1/8"	156.32	-	-	123.80	-	-	115.62	80.97	168.33	136.96
5"	5-1/8"	241.05	-	-	181.55	-	-	184.46	165.92	308.61	308.97
6"	6-1/8"	357.06	-	-	246.54	-	-	250.69	230.10	445.52	339.33
8"	8-1/8"	668.52	-	-	471.95	-	-	475.21	-	855.89	637.02

*NITROGEN CHARGED THROUGH 3-1/8" ONLY

REFRIGERATION SERVICE TUBE / PRICE PER COIL

O.D. Sizes	1/8"	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	7/8"	1-1/8"	1-3/8"	1-5/8"
50 Foot Coil	80.78	94.43	107.58	145.87	152.09	216.38	289.62	345.54	512.84	768.29	1,314.20	1,668.38
100 Foot Coil	166.59	194.76	223.75	300.66	325.69	450.06	602.35	724.59	1,081.04	1,582.74	2,707.18	3,436.80

TEMPERATURE CONTROL TUBE / PRICE PER FOOT

NOT RECOMMENDED FOR BENDING OR FORMING PURPOSES. ORDER QUANTITY IS IN 2000 FEET PER BOX INCREMENTS.

HARD			SOFT			HARD			SOFT		
O.D.	Wall	Price/Ft	O.D.	Wall	Price/Ft	O.D.	Wall	Price/Ft	O.D.	Wall	Price/Ft
1/4"	0.025	3.68	1/4"	0.025	4.82	1/4"	0.032	4.30	1/4"	0.032	5.63

REFERENCE INFORMATION

COPPER TUBE

		Type K		Type L / ACR		Type M		DWV	
STANDARD LENGTHS*		HARD COILS 20' Lengths 60' – through 1-1/2" 100' – through 1-1/4" 40' and 60' – 2" only		HARD COILS 20' Lengths 60' – through 1-1/2" 100' – through 1-1/4" 40' – 2" only		HARD COILS 20' Lengths Consult		HARD 20' Lengths	
NOM	O.D.	WALL	WGT/FT	WALL	WGT/FT	WALL	WGT/FT	WALL	WGT/FT
1/8"	1/4"	–	–	0.025	0.068	–	–	–	–
1/4"	3/8"	0.035	0.145	0.030	0.126	0.025	0.106	–	–
3/8"	1/2"	0.049	0.269	0.035	0.198	0.025	0.145	–	–
1/2"	5/8"	0.049	0.344	0.040	0.285	0.028	0.204	–	–
5/8"	3/4"	0.049	0.418	0.042	0.362	0.030	0.263	–	–
3/4"	7/8"	0.065	0.641	0.045	0.455	0.032	0.328	–	–
1"	1-1/8"	0.065	0.839	0.050	0.655	0.035	0.465	–	–
1-1/4"	1-3/8"	0.065	1.04	0.055	0.884	0.042	0.682	0.040	0.650
1-1/2"	1-5/8"	0.072	1.36	0.060	1.14	0.049	0.940	0.042	0.809
2"	2-1/8"	0.083	2.06	0.070	1.75	0.058	1.46	0.042	1.07
2-1/2"	2-5/8"	0.095	2.93	0.080	2.48	0.065	2.03	–	–
3"	3-1/8"	0.109	4.00	0.090	3.33	0.072	2.68	0.045	1.69
3-1/2"	3-5/8"	0.120	5.12	0.100	4.29	0.083	3.58	–	–
4"	4-1/8"	0.134	6.51	0.110	5.38	0.095	4.66	0.058	2.87
5"	5-1/8"	0.160	9.67	0.125	7.61	0.109	6.66	0.072	4.43
6"	6-1/8"	0.192	13.90	0.140	10.20	0.122	8.92	0.083	6.10
8"	8-1/8"	0.271	25.90	0.200	19.30	0.170	16.46	–	–

*FOR SPECIAL LENGTHS OR TEMPER CONSULT FOR PRICE AND AVAILABILITY.

REFRIGERATION SERVICE TUBE

O.D.	WALL THICKNESS	WEIGHT PER FOOT	WEIGHT PER COIL*	COIL DIAMETER	COILS PER MASTER	WEIGHT PER MASTER
1/8"	0.030	0.0347	1.74	14-3/4"	10	17.4
3/16"	0.030	0.0575	2.83	14-3/4"	10	28.80
1/4"	0.030	0.0804	4.02	14-3/4"	10	40.20
5/16"	0.032	0.109	5.45	14-3/4"	10	54.50
3/8"	0.032	0.134	6.70	16-1/2"	10	67.00
1/2"	0.032	0.182	9.10	20"	5	45.50
5/8"	0.035	0.251	12.55	22"	5	62.75
3/4"	0.035	0.305	15.25	25"	3	45.75
7/8"	0.045	0.455	22.75	27-1/2"	3	22.75
1-1/8"	0.050	0.655	32.75	34-1/2"	–	32.75
1-3/8"	0.055	0.884	44.20	39-1/2"	–	44.20
1-5/8"	0.060	1.14	57.00	42"	–	57.00

*STANDARD 50' COIL. 100' COILS ALSO AVAILABLE AS STANDARD STOCK ITEM.

TEMPERATURE CONTROL TUBE

PACKED 2000' PER BOX

O.D.	WALL	WGT/FT
1/4"	0.025	0.0685

O.D.	WALL	WGT/FT
1/4"	0.032	0.0849

PLASTIC COATED COPPER TUBE

Polyethylene coating made from low density LDPE resin and is extruded at 0.025" minimum wall.