

**WATER TUBE/PRICE PER FOOT**

Diameter		Type K			Type L			Type M	DWV	Nitrogen Charged* ACR/MED	
NOM	O.D.	Hard Lengths	Soft Coils	Soft Lengths	Hard Lengths	Soft Coils	Soft Lengths	Hard Lengths	Hard Lengths	Type K	Type L
1/8"	1/4"	-	-	-	-	-	-	-	-	-	4.69
1/4"	3/8"	3.76	3.91	4.76	3.30	3.32	4.26	-	-	4.05	3.56
3/8"	1/2"	6.75	7.06	7.96	4.83	4.94	6.64	3.82	-	7.11	5.35
1/2"	5/8"	7.92	8.62	10.02	5.89	7.20	8.83	4.35	-	8.27	6.92
5/8"	3/4"	9.75	10.65	11.93	8.47	9.22	11.42	6.34	-	10.39	9.25
3/4"	7/8"	14.48	16.07	18.47	9.61	11.46	13.54	7.04	-	15.43	11.01
1"	1-1/8"	18.83	21.34	24.42	14.09	16.42	18.77	10.81	-	19.66	15.83
1-1/4"	1-3/8"	23.64	26.16	29.02	19.50	22.28	24.90	16.19	17.11	24.51	21.10
1-1/2"	1-5/8"	31.19	33.99	40.30	24.82	28.69	33.59	22.27	21.46	32.92	27.41
2"	2-1/8"	46.43	52.17	62.03	38.83	45.66	52.97	34.25	28.15	48.66	41.36
2-1/2"	2-5/8"	68.25	-	92.62	55.59	-	72.69	49.62	-	72.45	59.45
3"	3-1/8"	94.20	-	128.87	77.63	-	97.18	65.89	48.81	98.28	80.37
3-1/2"	3-5/8"	120.50	-	-	101.27	-	-	89.04	-	127.67	106.10
4"	4-1/8"	164.12	-	-	129.97	-	-	121.39	85.01	176.72	143.79
5"	5-1/8"	251.09	-	-	189.11	-	-	192.15	172.83	321.47	324.38
6"	6-1/8"	371.94	-	-	256.81	-	-	261.14	239.69	464.08	353.47
8"	8-1/8"	696.38	-	-	491.61	-	-	495.01	-	891.55	663.56

\*NITROGEN CHARGED THROUGH 3-1/8" ONLY

**REFRIGERATION SERVICE TUBE / PRICE PER COIL**

O.D. Sizes	1/8"	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	7/8"	1-1/8"	1-3/8"	1-5/8"
50 Foot Coil	84.81	99.14	112.94	153.14	159.67	227.17	304.06	362.77	538.41	806.60	1,379.74	1,751.58
100 Foot Coil	174.90	204.47	234.91	315.65	341.93	472.50	632.39	760.72	1,134.95	1661.67	2,842.18	3,608.19

**TEMPERATURE CONTROL TUBE / PRICE PER FOOT**

NOT RECOMMENDED FOR BENDING OR FORMING PURPOSES. ORDER QUANTITY IS IN 2000 FEET PER BOX INCREMENTS.

HARD			SOFT			HARD			SOFT		
O.D.	Wall	Price/Ft	O.D.	Wall	Price/Ft	O.D.	Wall	Price/Ft	O.D.	Wall	Price/Ft
1/4"	0.025	3.86	1/4"	0.025	5.06	1/4"	0.032	4.51	1/4"	0.032	5.91

# REFERENCE INFORMATION

## COPPER TUBE

		Type K		Type L / ACR		Type M		DWV	
STANDARD LENGTHS*		HARD COILS 20' Lengths 60' – through 1-1/2" 100' – through 1-1/4" 40' and 60' – 2" only		HARD COILS 20' Lengths 60' – through 1-1/2" 100' – through 1-1/4" 40' – 2" only		HARD COILS 20' Lengths Consult		HARD 20' Lengths	
NOM	O.D.	WALL	WGT/FT	WALL	WGT/FT	WALL	WGT/FT	WALL	WGT/FT
1/8"	1/4"	–	–	0.025	0.068	–	–	–	–
1/4"	3/8"	0.035	0.145	0.030	0.126	0.025	0.106	–	–
3/8"	1/2"	0.049	0.269	0.035	0.198	0.025	0.145	–	–
1/2"	5/8"	0.049	0.344	0.040	0.285	0.028	0.204	–	–
5/8"	3/4"	0.049	0.418	0.042	0.362	0.030	0.263	–	–
3/4"	7/8"	0.065	0.641	0.045	0.455	0.032	0.328	–	–
1"	1-1/8"	0.065	0.839	0.050	0.655	0.035	0.465	–	–
1-1/4"	1-3/8"	0.065	1.04	0.055	0.884	0.042	0.682	0.040	0.650
1-1/2"	1-5/8"	0.072	1.36	0.060	1.14	0.049	0.940	0.042	0.809
2"	2-1/8"	0.083	2.06	0.070	1.75	0.058	1.46	0.042	1.07
2-1/2"	2-5/8"	0.095	2.93	0.080	2.48	0.065	2.03	–	–
3"	3-1/8"	0.109	4.00	0.090	3.33	0.072	2.68	0.045	1.69
3-1/2"	3-5/8"	0.120	5.12	0.100	4.29	0.083	3.58	–	–
4"	4-1/8"	0.134	6.51	0.110	5.38	0.095	4.66	0.058	2.87
5"	5-1/8"	0.160	9.67	0.125	7.61	0.109	6.66	0.072	4.43
6"	6-1/8"	0.192	13.90	0.140	10.20	0.122	8.92	0.083	6.10
8"	8-1/8"	0.271	25.90	0.200	19.30	0.170	16.46	–	–

\*FOR SPECIAL LENGTHS OR TEMPER CONSULT FOR PRICE AND AVAILABILITY.

## REFRIGERATION SERVICE TUBE

O.D.	WALL THICKNESS	WEIGHT PER FOOT	WEIGHT PER COIL*	COIL DIAMETER	COILS PER MASTER	WEIGHT PER MASTER
1/8"	0.030	0.0347	1.74	14-3/4"	10	17.4
3/16"	0.030	0.0575	2.83	14-3/4"	10	28.80
1/4"	0.030	0.0804	4.02	14-3/4"	10	40.20
5/16"	0.032	0.109	5.45	14-3/4"	10	54.50
3/8"	0.032	0.134	6.70	16-1/2"	10	67.00
1/2"	0.032	0.182	9.10	20"	5	45.50
5/8"	0.035	0.251	12.55	22"	5	62.75
3/4"	0.035	0.305	15.25	25"	3	45.75
7/8"	0.045	0.455	22.75	27-1/2"	3	22.75
1-1/8"	0.050	0.655	32.75	34-1/2"	–	32.75
1-3/8"	0.055	0.884	44.20	39-1/2"	–	44.20
1-5/8"	0.060	1.14	57.00	42"	–	57.00

\*STANDARD 50' COIL. 100' COILS ALSO AVAILABLE AS STANDARD STOCK ITEM.

## TEMPERATURE CONTROL TUBE

PACKED 2000' PER BOX

O.D.	WALL	WGT/FT
1/4"	0.025	0.0685

O.D.	WALL	WGT/FT
1/4"	0.032	0.0849

## PLASTIC COATED COPPER TUBE

Polyethylene coating made from low density LDPE resin and is extruded at 0.025" minimum wall.