

**WATER TUBE/PRICE PER FOOT**

Diameter		Type K			Type L			Type M	DWV	Nitrogen Charged* ACR/MED	
NOM	O.D.	Hard Lengths	Soft Coils	Soft Lengths	Hard Lengths	Soft Coils	Soft Lengths	Hard Lengths	Hard Lengths	Type K	Type L
1/8"	1/4"	-	-	-	-	-	-	-	-	-	4.34
1/4"	3/8"	3.47	3.61	4.39	3.05	3.07	3.94	-	-	3.74	3.29
3/8"	1/2"	6.24	6.52	7.35	4.46	4.57	6.13	3.53	-	6.57	4.95
1/2"	5/8"	7.31	7.96	9.25	5.44	6.65	8.16	4.02	-	7.64	6.39
5/8"	3/4"	9.01	9.84	11.02	7.83	8.52	10.55	5.86	-	9.60	8.55
3/4"	7/8"	13.38	14.85	17.06	8.88	10.59	12.51	6.51	-	14.26	10.18
1"	1-1/8"	17.40	19.72	22.56	13.02	15.17	17.34	9.99	-	18.17	14.63
1-1/4"	1-3/8"	21.84	24.17	26.81	18.01	20.58	23.01	14.96	15.81	22.65	19.50
1-1/2"	1-5/8"	28.82	31.41	37.24	22.93	26.51	31.03	20.57	19.83	30.42	25.33
2"	2-1/8"	42.89	48.20	57.31	35.88	42.19	48.94	31.64	26.01	44.96	38.22
2-1/2"	2-5/8"	63.06	-	85.57	51.36	-	67.16	45.84	-	66.94	54.93
3"	3-1/8"	87.04	-	119.07	71.72	-	89.78	60.88	45.01	90.80	74.25
3-1/2"	3-5/8"	111.34	-	-	93.57	-	-	82.27	-	117.96	98.03
4"	4-1/8"	151.63	-	-	120.09	-	-	112.15	78.54	163.28	132.85
5"	5-1/8"	233.82	-	-	176.10	-	-	178.93	160.94	299.35	299.70
6"	6-1/8"	346.35	-	-	239.14	-	-	243.17	223.20	432.15	329.15
8"	8-1/8"	648.46	-	-	457.79	-	-	460.95	-	830.21	617.91

\*NITROGEN CHARGED THROUGH 3-1/8" ONLY

**REFRIGERATION SERVICE TUBE / PRICE PER COIL**

O.D. Sizes	1/8"	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	7/8"	1-1/8"	1-3/8"	1-5/8"
50 Foot Coil	78.36	91.60	104.35	141.49	147.53	209.89	280.93	335.17	497.45	745.24	1,274.77	1,618.33
100 Foot Coil	161.59	188.92	217.04	291.64	315.92	436.56	584.28	702.85	1,048.61	1,535.26	2,625.96	3,333.70

**TEMPERATURE CONTROL TUBE / PRICE PER FOOT**

NOT RECOMMENDED FOR BENDING OR FORMING PURPOSES. ORDER QUANTITY IS IN 2000 FEET PER BOX INCREMENTS.

HARD			SOFT			HARD			SOFT		
O.D.	Wall	Price/Ft	O.D.	Wall	Price/Ft	O.D.	Wall	Price/Ft	O.D.	Wall	Price/Ft
1/4"	0.025	3.57	1/4"	0.025	4.68	1/4"	0.032	4.17	1/4"	0.032	5.46

# REFERENCE INFORMATION

## COPPER TUBE

		Type K		Type L / ACR		Type M		DWV	
STANDARD LENGTHS*		HARD COILS 20' Lengths 60' – through 1-1/2" 100' – through 1-1/4" 40' and 60' – 2" only		HARD COILS 20' Lengths 60' – through 1-1/2" 100' – through 1-1/4" 40' – 2" only		HARD COILS 20' Lengths Consult		HARD 20' Lengths	
NOM	O.D.	WALL	WGT/FT	WALL	WGT/FT	WALL	WGT/FT	WALL	WGT/FT
1/8"	1/4"	–	–	0.025	0.068	–	–	–	–
1/4"	3/8"	0.035	0.145	0.030	0.126	0.025	0.106	–	–
3/8"	1/2"	0.049	0.269	0.035	0.198	0.025	0.145	–	–
1/2"	5/8"	0.049	0.344	0.040	0.285	0.028	0.204	–	–
5/8"	3/4"	0.049	0.418	0.042	0.362	0.030	0.263	–	–
3/4"	7/8"	0.065	0.641	0.045	0.455	0.032	0.328	–	–
1"	1-1/8"	0.065	0.839	0.050	0.655	0.035	0.465	–	–
1-1/4"	1-3/8"	0.065	1.04	0.055	0.884	0.042	0.682	0.040	0.650
1-1/2"	1-5/8"	0.072	1.36	0.060	1.14	0.049	0.940	0.042	0.809
2"	2-1/8"	0.083	2.06	0.070	1.75	0.058	1.46	0.042	1.07
2-1/2"	2-5/8"	0.095	2.93	0.080	2.48	0.065	2.03	–	–
3"	3-1/8"	0.109	4.00	0.090	3.33	0.072	2.68	0.045	1.69
3-1/2"	3-5/8"	0.120	5.12	0.100	4.29	0.083	3.58	–	–
4"	4-1/8"	0.134	6.51	0.110	5.38	0.095	4.66	0.058	2.87
5"	5-1/8"	0.160	9.67	0.125	7.61	0.109	6.66	0.072	4.43
6"	6-1/8"	0.192	13.90	0.140	10.20	0.122	8.92	0.083	6.10
8"	8-1/8"	0.271	25.90	0.200	19.30	0.170	16.46	–	–

\*FOR SPECIAL LENGTHS OR TEMPER CONSULT FOR PRICE AND AVAILABILITY.

## REFRIGERATION SERVICE TUBE

O.D.	WALL THICKNESS	WEIGHT PER FOOT	WEIGHT PER COIL*	COIL DIAMETER	COILS PER MASTER	WEIGHT PER MASTER
1/8"	0.030	0.0347	1.74	14-3/4"	10	17.4
3/16"	0.030	0.0575	2.83	14-3/4"	10	28.80
1/4"	0.030	0.0804	4.02	14-3/4"	10	40.20
5/16"	0.032	0.109	5.45	14-3/4"	10	54.50
3/8"	0.032	0.134	6.70	16-1/2"	10	67.00
1/2"	0.032	0.182	9.10	20"	5	45.50
5/8"	0.035	0.251	12.55	22"	5	62.75
3/4"	0.035	0.305	15.25	25"	3	45.75
7/8"	0.045	0.455	22.75	27-1/2"	3	22.75
1-1/8"	0.050	0.655	32.75	34-1/2"	–	32.75
1-3/8"	0.055	0.884	44.20	39-1/2"	–	44.20
1-5/8"	0.060	1.14	57.00	42"	–	57.00

\*STANDARD 50' COIL. 100' COILS ALSO AVAILABLE AS STANDARD STOCK ITEM.

## TEMPERATURE CONTROL TUBE

PACKED 2000' PER BOX

O.D.	WALL	WGT/FT
1/4"	0.025	0.0685

O.D.	WALL	WGT/FT
1/4"	0.032	0.0849

## PLASTIC COATED COPPER TUBE

Polyethylene coating made from low density LDPE resin and is extruded at 0.025" minimum wall.